Filter Multiport Valve

TESTED 100% WATERTIGHT

Top mount and side mount versions



Material

Sturdy ABS & Marine-Grade Stainless Stee

Pool & Spa Equipment


Multiport Valve

Topguy Valves are produced in versions for Top Mount and Side Mount filter designs and are made of ABS material with heavy - duty plastic handle. Depending on filter type, 6 - way and 8 - way models are available for operating functions to cover all the necessary operations needed in any swimming pools filtration.


Product Features

- 1. 100% tested for pressure and watertightness
- 2. Easy installation, maintenance, and servicing
- 3. Constructed with sturdy ABS and marine-grade stainless steel
- 4. Designed for superior durability
- 5. Commercial multiport valves are cost
 efficient and space-saving compareed to the
 butterfly valve manifolds


Functions: 6-Way Multiport Valve



Functions: 8-Way Multiport Valve



Top Mount Multiport Valve



Top Mount Multiport Valve

Connection

Thread Type

Max Working Pressure

200kPa/28psi/2bar

Factory Testing Pressure

350kPa/50psi/3.5bar

Max Water Temperature

50°C (122°F)

Flow Rate

19m3/h at 200kPa/28psi/2bar

Description Valve only Model MPV-01/MPV-02

1.5 inch 8-Way Top Mount Valve



Top Mount Multiport Valve

Connection

Thread Type

Max Working Pressure

200kPa/28psi/2bar

Factory Testing Pressure

350kPa/50psi/3.5bar

Max Water Temperature

50°C (122°F)

Flow Rate

42m³/h at 200kPa/28psi/2bar

Model

MPV-01/MPV-02

Description

Valve only

2 inch 6-Way Top Mount Valve



Side Mount Multiport Valve



Side Mount Multiport Valve

Connection

Union Connection

Max Working Pressure

200kPa/28psi/2bar

Factory Testing Pressure

350kPa/50psi/3.5bar

Max Water Temperature

50°C (122°F)

Flow Rate

19m3/h at 200kPa/28psi/2bar

Model

MPV-03/MPV-04

Description Valve only

1.5 inch 8-Way Side Mount Valve



Side Mount Multiport Valve

Connection

Union Connection

Max Working Pressure

200kPa/28psi/2bar

Factory Testing Pressure

350kPa/50psi/3.5bar

Max Water Temperature

50°C (122°F)

Flow Rate

42m³/h at 200kPa/28psi/2bar

Model

MPV-03/MPV-04

Description Valve only

2 inch 6-Way Side Mount Valve

